

## Tubing Group

### Norprene® Elastomer Tubing



High quality multi-purpose tubing.

Excellent flexural fatigue characteristics.

Can be used for peristaltic pump applications.

Temperature range -75°F to 275°F (-59°C to 135°C)

Construction: Black 61 durometer non-reinforced synthetic compound.

Also available in white food grade.

Standard length is 50 feet.

<b>Tubing Group</b>				
<b>Norprene® Tubing ( 50 ft coils)</b>				
<b>Part Number</b>	<b>ID Size</b>	<b>OD Size</b>	<b>Weight in lbs</b>	<b>Price</b>
TU-NORPRENE-02-01	1/8"	0.250"	1 1/2	\$ 56.00
TU-NORPRENE-03-01	3/16"	0.312"	2	\$ 61.00
TU-NORPRENE-04-01	1/4"	0.375"	2.5	\$ 68.00
TU-NORPRENE-04-02	1/4"	0.500"	3.5	\$ 165.00
TU-NORPRENE-05-01	5/16"	0.437"	3	\$ 87.00
TU-NORPRENE-06-01	3/8"	0.500"	5	\$ 91.00
TU-NORPRENE-06-02	3/8"	0.625"	8.5	\$ 217.00
TU-NORPRENE-08-02	1/2"	0.750"	10	\$ 272.50
TU-NORPRENE-10-02	5/8"	0.875"	11	\$ 328.00
TU-NORPRENE-12-02	3/4"	1.000"	13	\$ 377.00
TU-NORPRENE-16-02	1"	1.250"	15	\$ 486.00

**Sold in Full Coils Only**